


POWER TRANSMISSION CHAIN COUPLINGS

optibelt **CHAIN COUPLING**

- High performance
- Low maintenance
- High torque
- Durable



Contact an Applied ® representative today!



COUPLING	CHAIN TYPE	STRAIGHT BORE		TORQUE RATINGS	MAX RPM	WEIGHT
		MIN	MAX	Nm	WITH COVER	
4012	40-2	12	20	210	5000	1.0
4016	40-2	14	30	380	5000	1.7
5016	50-2	16	40	725	4000	2.3
5018	50-2	16	45	925	4000	2.7
6018	60-2	20	55	1750	3000	4.5
6020	60-2	20	70	2050	3000	5.6
6022	60-2	25	75	2400	2500	10.4
8018	80-2	30	75	3800	2000	14.1
8020	80-2	30	85	4700	2000	15.2
8022	80-2	35	95	5500	1800	21.8
10020	100-2	40	110	8700	1800	36.3
12018	120-2	40	120	13250	1600	49.9
12022	120-2	40	150	17800	1200	69.1

DIMENSION SHEET

COUPLING	CASE O.D	WIDTH	CASE WIDTH	HUB WIDTH	HUB SPACE	HUB DIAMETER
	A	B	C	D	E	F
4012	78	78	72	36	6	31
4016	92	80	75	36	8	50
5016	111	100	85	45	10	60
5018	123	100	85	45	10	70
6018	144	122	106	54	14	85
6020	160	123	108	54	15	98
6022	168	123	116	54	15	110
8018	190	149	128	67	15	110
8020	211	149	138	67	15	120
8022	226	149	138	67	15	140
10020	280	176	155	79	18	160
12018	305	198	180	89	20	170
12022	335	218	180	99	20	210